

StandCharger Technical Specification

Input	Input AC Voltage	100-240V / 47-63 Hz
	AC Adapter Input Current	0 to 2 Amps
Output	Output Ports	7 USB Female Type A Ports
	AC to DC Adapter Efficiency	95%
	StandChargerEfficiency	85-95%
	Total Output Wattage	84 Watts
	Output Voltage	4.80V – 5.10V
	Total Output Current(Max)	16.8 Amps
	Total Output Current (per port)	2.4 Amps
	Smart Charger Emulation	USB BC 1.2, USB BC 1.1, Apple Proprietary, Samsung Proprietary
Regulatory	Certifications	AC Adapter is UL, FCC, CE and RoHS Certified.
Mechanical	Dimension/WeightStandCharger	7.48 x 5.51 x 2.62 inches / 0.83 lbs
	Dimension/WeightAC Adapter	5.25 x 2.30 x 1.20 inches / 0.85 lbs
	AC Adapter Cable Length	3.3 feet Adapter to SmartCharger/ 3.9 feet AC outlet to Adapter
	AC Plug Pin Format	USA 3 Pin Plug
	Cooling	Fan-less Passive (No Noise)
Environmental	Operating Temperature	0 to 35°C
	Storage Temperature	-10°C to 45°C
Compatibility	Apple	iPhone (all models), iPad (all models), iPod (all models)
	Samsung	Galaxy Phone(all models), Note Phones (all models), Galaxy Tab (all models) & other smartphones/tablets.
	LG, HTC, Motorola, Nokia, Sony Ericsson & many other brands.	Almost all smartphones & tablets.
	Go Pro	All USB chargeable camcorder/cameras
	Other Brands	Almost all USB chargeable devices like Bluetooth headset, GPS etc.
Box Contents	StandCharger, AC/DC Power Adapter, Help Card, Warranty Card & User Manual.	

